

In-Line Fluid Valves and Swivels

High Pressure Swivels

Used to provide free movement of hose sections without kinking or pressure bleeding from valves or spray guns.

Part No.	Inlet/Outlet	Max WPR			Packings	Wetted Parts	Inst. Manual	Service Kit
		psi	bar	MPa				
204083	1/4 npt(m) 1/8 npt(f)	8000	551	55.1	Leather	Steel-plated	306708	–
204084	1/4 npt(m) 1/4 npt(f)	8000	551	55.1	Leather	Steel-plated	306708	–
214925	1/4 npsm(f) 3/8 npt(f)	5000	345	34.5	Leather	Steel-plated	306861	–
207946	1/2 npsm(f) 3/8 npt(f)	6000	413	41.3	Polyurethane	Steel-plated	307005	–
207947	1/2 npt(f) 1/2 npt(m)	6000	413	41.3	Polyurethane	Steel-plated	307005	–
239663	1/4 npt(m) 1/4 npsm(f)	3600	248	24.8	Leather	Steel-plated	306861	207839
223341	1/4 npt(m) 1/4 npsm(f) Same as 239663 except Teflon packed.	3600	248	24.8	Teflon	Steel-plated	306861	223342
214926	1/2 npsm(f) 3/8 npt(f)	5000	345	34.5	Leather	Steel-plated	306861	–
• 236987	1/4 npsm(f) 1/4 npt(f)	7400	510	51.0	Filled PTFE	SST	306861	–
224457	1/4 npt(m) 1/4 npsm(f) Same as 239663 except card mounted.	3000	207	20.7	–	–	–	–
• 239394	1/4 npsm(m) 1/4 npsm(f) Includes: filter chamber and 100 mesh tip filter (205264).	5800	400	40.0	Teflon	SST	–	–
• 189018	Same as 239394 except without filter chamber and tip filter.							


• *Waterborne compatible*

High Pressure 3-way Z-Type Swivels


Used to allow free movement of dispense valves and prevent hose tangles.

Part No.	Inlet/Outlet npt	Max WPR			Packings	Wetted Parts	Inst. Manual
		psi	bar	MPa			
202579	1/8 (m) 1/4 (f)	6500	448	44.8	Leather	Steel-plated	306708
202577	1/4 (m) 1/4 (f)	6500	448	44.8	Leather	Steel-plated	306708
223340	1/4 (m) 1/4 (f)	6500	448	44.8	Teflon	Steel-plated	–
207948	1/2 (m) 1/2 (f)	6000	413	41.3	Polyurethane	Steel-plated	307005


Caution: Z-swivels to be used with non-abrasive fluids only.




204083




239663



223341



239394



**202579
202577
223340**